

---

---

# Polyform Mooring Buoys

---

---



---

## POLYFORM MOORING BUOYS

Available white with blue stripe or florescent red.

Model CM-2: 14" diameter x 29" length  
Buoyancy: 55 lbs.  
One per carton, 11 lbs.

Model CM-3: 18.5" diameter x 35" length  
Buoyancy: 121 lbs.  
One per carton, 13 lbs.

The CM Series Mooring Buoy has been designed to provide the ultimate in strength, durability, and versatility. With up to 35% more buoyancy than hard shell buoys, the CM can handle larger chain sizes – providing increased security to any mooring. The mooring iron is galvanized and additionally protected with a vinyl-coated eye. A larger eye (4 3/8" diameter) and swivel (1 1/2" diameter) along with a 5/8" center tube provide maximum strength. And the CM's soft vinyl surface won't harm boat finishes

Polyform buoys can be inflated either with the Polyform hand pump or almost any form of compressed air that will cover the valve. An inflation adapter is available for use with standard compressor nozzles or hand pumps. Designed to be inflated to 2.1 lbs./0.15 bar of pressure at 68 degrees F. When inflating without pressure gauge, fill the buoy until the walls are fully expanded, but make certain you can depress the wall at least 1/4" with light hand pressure. Over inflation will reduce performance of the product.

