

---

---

# Line Storage Mooring Buoys

---

---



---

## LINE STORAGE MOORING BUOYS ITEM NO. 15-60

### Features:

- A super-tough, low-density, polyethylene shell that is ultraviolet inhibited for weather resistance.
- 2 inch blue band for visibility and to conform to Coast Guard regulations
- ½" rounded lip on top section to prevent mooring line chafing
- 5/16" bolt at the top of the PVC pipe to secure the chain

**Specifications:** Buoyancy: 170 lbs, Height: 18 inches, Diameter: 24 inches, Weight: 16 lbs

A mooring line can become slimy with seaweed and encrusted with mussels and barnacles while floating in the water. When tying up a boat, barnacles can cut a hand, and a slimy mooring line can make a mess on the fore deck. The **Line Storage Buoy** solves these problems. It features a visible top section, complete with drain holes, to coil the mooring line keeping it clean and dry. Because of its cylindrical shape, the new buoy can use all of its floatation capacity. 170 lbs is its maximum buoyancy, with the foam completely submerged and still sticking out of the water a full 6 inches to meet local harbormaster and Coast Guard requirements.

The mooring line is shackled to chain inside and below the edge of the line storage area portion of the buoy, preventing the boat from being damaged by the metal shackle. This can occur with conventional buoys when certain wind and tide combinations cause the boat to climb on top of its mooring causing damage to paint and fiberglass from the metal shackle.

