

---

---

# Mooring Anchors

---

---

---

## CONCRETE MOORING ANCHOR



Complete with Hot Dipped Galvanized Eye.

ITEM NO.	WEIGHT
15-46	45 lbs.
15-47	90
15-48	180
--	300

---

## TIDE MASTER ITEM NO. 15-061



Anchoring System for Channel Markers and Regulator Buoys

Includes complete stainless steel suspension system with bronze pulleys and attachment arm with 3 heavy-duty nylon thimbles to prevent electrolysis at all connections and a 40 lb. counterweight. Also included and charged by the foot is the 1/8" diameter #316 alloy, stainless steel cable. The length of cable required is determined by the depth of the water at highest tide plus 4 feet. The factory will cut and swage loops on both ends of the cable for easy attachment at no charge.

Designed for use where minimum drift anchoring is required. The Tide Master anchoring system will help to stabilize and maintain position for all channel markers and regulatory buoys with minimum drift to either side during tidal movement and current flow.

How it works: The unique design incorporates a stainless steel cable that is attached to the buoy anchor and then passes through the stainless steel bracket/pulley assembly hooked to the base of the buoy. The other end of the cable is fastened to a 40 lb. counterweight. During actual use, the counterweight shifts up and down in response to tidal movements and current flow and the buoy's position remains relatively unaffected.

