


Rolyan Can Buoys

These can buoys are urethane foam filled with a sturdy ABS hull. They are ultraviolet inhibited and self-righting without mooring. Symbols and messages are available for white buoys and come with a 3" reflective band – silver on white buoys, green on green buoys and red on red buoys.

STANDARD CANS





Widely used by the U.C. Corps of Engineers, these cans have a concrete ballast encased in ABS. The ballast is attached by a galvanized steel pipe.


ITEM NO.		--	--	--	--
MODEL		B1251	B1352	B1452	B2445
Can Diameter and Height	In.	12x51	13x52	14x52	24x45
Overall Height	In.	73.5	76	86	97
Daymark with 36" Exposure	Sq. Ft.	3.0	3.3	3.5	6.0
Exposure without Tackle	In.	38	40	40	38
Mooring Tackle Allowable for 36" Exposure	Lbs.	7	18	22	18
Draft	In.	36	35	44	57
Submerged Buoyancy	Lbs.	155	190	220	624
Net Weight	Lbs.	71	79	90	138
Shipping Weight	Lbs.	80	86	96	148

FLOAT COLLAR CANS

B1428SW



B1428UL



Excellent stability in wind and current. There is a choice of symbols and messages.

ITEM NO.		--	--	--
MODEL		B1428SW	B1428FW	B1428UL
Can Diameter and Height	In.	14x30	14x30	14x30
Float Collar Diameter and Height	In.	28x12	28x12	28x12
Overall Height	In.	49	49	89
Daymark with 36" Exposure	Sq. Ft.	4.1	4.1	4.1
Mooring Tackle Allowable for 36" Exposure	Lbs.	29	40	29
Draft	In.	Under 9	Under 6	51
Submerged Buoyancy	Lbs.	320	340	350
Net Weight	Lbs.	105	93	120
Shipping Weight	Lbs.	135	135	145



B1428SW – Internal ballast – bottom attachment

B1428FW – Internal ballast – side attachment


B1428UL – Heavy-duty – external ballast

COAST GUARD TYPE

B6CPRM
B5CPRM



B5CPRSW



These cans are for heavy-duty applications and include an internal radar reflector.

ITEM NO.		--	--	--
MODEL		B6CPRM ½ Mile Buoy	B5CPRM 1 Mile Buoy	B5CPRFW B5CPRSW
Can Diameter and Height	In.	12x21	19x33	19x33
Collar Diameter and Height	In.	28x12	38x13	38x13
Overall Height	In.	56.3	84.5	50
Daymark without Mooring	Sq. Ft.	3.5	7.5	
Buoyancy/In. Submerged	Lbs.	22.2	41	39
Draft	In.	24	39	9
Submerged Buoyancy	Lbs.	287	815	700
Net Weight	Lbs.	83	124	164
Shipping Weight	Lbs.	90	140	209

B5CPRSW – Internal ballast – bottom attachment

B5CPRFW – Internal ballast – side attachment

B6CPRM – Heavy-duty – external ballast

B5CPRM – (1 mile buoy)



HENDERSON MARINE SUPPLY, INC.

800-523-1586 www.hendersonmarine.com

Specifications subject to change without notice. Not responsible for rust.

Page 15-4

Last Updated: 3/24/2003 9:58:00 AM