
Aluminum Dockside Electrical Power Pedestals



Standard Dockside Electrical Pillars

Standard Features

- Dimensions: 8" x 8" x 41"(Height)
- Casing: Maximum six receptacles (9 poles)
- Extruded marine grade aluminum 6063 with 3/16" wall thickness. No seams
- Welded base for extra strength
- All stainless steel fasteners with nylon washers
- Isolation plate to separate water, telephone and TV from "electrical" (completely waterproof)
- Each receptacle protected by a thermal magnetic circuit breaker
- Marine grade electrical receptacles are available in 20 amp duplex GFI and 20, 30 & 50 amp twist-lock , 100 amp single & three phase - pin and sleeve
- Electrical distribution block - direct feed
- Lenses for the lights are on three sides and are made of lexan
- Cone top
- Powder coated white inside and outside
- **15 year unconditional warranty on structural integrity of casing**
- Listed by qualified testing agency

Options

- Power block - loop feed (stud) - maximum wire size 500 MCM cable
- TV/telephone receptacle
- PL-9 fluorescent light & photo cell
- Thermo plastic receptacle covers
- Aluminum covers with receptacle mounted on a 45° down angle and back lighted.
- Electric meters
- Water meters with locking ball valves available on 45" unit
- 45" height and widths to 16"
- Hose holders / cable brackets
- European power receptacles
- 277/480V Receptacles available
- Natural aluminum finish and custom colors available
- Custom pillar available



HENDERSON MARINE SUPPLY, INC.

800-523-1586 www.hendersonmarine.com

Specifications subject to change without notice. Not responsible for rust.

Liability limited to product replacement at the option of Henderson Marine Supply, Inc.

Not responsible for any inaccuracies in specifications.

Page 12-18-1

Last Updated: 10/9/2007 12:01:00 AM

Piling Mounted Electrical Power Center

| | |
|--|--|
| Standard Features <ul style="list-style-type: none">• Dimensions: 6" x 6" x 21"(Height)• Casing: Maximum three receptacles (6 poles)• Extruded aluminum 6063 with 1/8" wall thickness. No seams.• All stainless steel fasteners with nylon washers.• Each receptacle protected by a thermal magnetic circuit breaker• Marine grade electrical receptacles are available in 20 amp duplex GFI and 20, 30 & 50 amp twist-lock• Electrical distribution block - direct feed• Lenses for the lights are on three sides and are made of lexan• Thermo plastic receptacle covers• Cone top• Brackets for either round or square pilings• Powder coated white inside and outside• 15 year unconditional warranty on structural integrity of casing• Listed by qualified testing agency | Options <ul style="list-style-type: none">• TV/telephone receptacle• PL-7 fluorescent light & photo cell• Natural aluminum finish and custom colors available• Electrical Meters |
|--|--|

Slim Line Dockside Electrical Pillars

| | |
|--|--|
| Standard Features <ul style="list-style-type: none">• Dimensions: 6" x 6" x 36"(Height)• Casing: Maximum four receptacles (6 poles)• Extruded aluminum 6063 with 1/8" wall thickness. No seams.• Welded base for extra strength• All stainless steel fasteners with nylon washers• Isolation plate to separate water, telephone and TV from "electrical" (completely waterproof)• Each receptacle protected by a thermal magnetic circuit breaker• Marine grade electrical receptacles are available in 20 amp duplex GFI and 20, 30 & 50 amp twist-lock• Electrical distribution block - direct feed• Lenses for the lights are on three sides and are made of lexan• Cone top• Powder coated white inside and outside• 15 year unconditional warranty on structural integrity of casing• Listed by qualified testing agency• | Options <ul style="list-style-type: none">• Power block - loop feed (stud) - maximum wire size 250 MCM cable• TV/telephone receptacle• PL-7 fluorescent light & photo cell• Thermo plastic receptacle covers• Aluminum covers with receptacle mounted on a 45° down angle and back-lighted• Electric meters• Hose holders / cable brackets• Natural aluminum finish and custom colors available• Custom pillars available |
|--|--|



HENDERSON MARINE SUPPLY, INC.
800-523-1586 www.hendersonmarine.com

Specifications subject to change without notice. Not responsible for rust.
Liability limited to product replacement at the option of Henderson Marine Supply, Inc.
Not responsible for any inaccuracies in specifications.

Page 12-18-2
Last Updated: 10/9/2007 12:01:00 AM